

# Portable COB LED Flood Lights





#### **Specification:**

- Nicely tieated die-casting ADC12 aluminum alloy housing
- 4mm tempered glass cover, strong protection and good optical function
- Waterproof:IP65
- Operating Temperature: -20-50°C
- Storage Temperature: -40-60°C

#### **Application:**

Play Ground, Construction Building, Garden or Park



www.eneltec-led.com



### Lamp Body

Using intergrated casting aluminum materials. crush resistance, fashionable & good gloss.

### **Top Facing**

High strength tempered glass lens Uniform light, high light transmittance; Cover theSpray paint grinding technology, elegant appearance, not rust.

#### Radiator

The integration die-casting radiator. Strong convection design is better to heat dissipation, Effective guarantee the lamp bead life.





## **Fittings**

H base fixed can be placed in any emergency auxiliary lighting, Match travel charger and car charger, More convenient.



ntegrative radia





**Car charger** 



#### Waterproof rubber plug

Waterproof design care every detail, waterproof grade IP65, better application in a harsh environment,



**Travel charger** Travel charger volume is relatively small easy to carry.



- 1.Holder
- Fixing screw
  Swivelling mounting bracket (u-shaped)
- 4. Stand
- 5. Locking screw for stand 6. On/Off switch 7. Charging socket







### Data

Model No.	ENFL-10W-01POR	ENFL-20W-01POR
Power (W)	10	20
Lumen (Im)	900	1800
CRI	>70	
Beam Angle	120°	
Color	3000K / 6000K	
IP Grade	IP65	
LED	Sanan 30mil	
LED Driver	CE Driver	
Battery	2400mA 3 hours working	4400mA 3 hours working
Product Dimension (mm)	115×110×250	180×125×270
Packing Dimension (mm)	12PCS 465×385×380	8PCS 455×375×570
Net Weight/ Gross Weight (Kg)	12PCS 11.4/12.5	8PCS 13.0/14.3