

ENELTEC[®]

brighten your ideas

SMD 3014 LED G24 Lights




LUMENMAX LED



Specifications:

- LED: Lumenmax SMD 3014
- Beam Angle: 120°
- Voltage: 85-265VAC
- Socket: G24/E27
- Color: 2800-3200K / 4000-4500K / 6000-6500K
- Operating temperature: -35 to + 50°C
- Material: Aluminium Alloy Die-cast Shape
- Light Degradation: < 5% in 20,000 hours
- Warranty: 3 years





Model	Dimension(mm) A*B
ENSP-6WG24-01(D)	35x35x120
ENSP-6WE27-01(D)	35x35x127
ENSP-7WG24-01(D)	35x35x120
ENSP-7WE27-01(D)	35x35x127
ENSP-10WG24-01(D)	35x35x160
ENSP-10WE27-01(D)	35x35x166
ENSP-12WG24-01(D)	35x35x160
ENSP-12WE27-01(D)	35x35x166

Applications:

High power LED bulbs are designed for use in supermarkets, jeweller's shops, advertisement box, office building, or for direct replacement of conventional lamps.

Features and advantages:

- Direct replacement of conventional lamps
- LED life of 50,000 hours continuous work
- No hazard of mercury or lead entering the environment
- Solid-state, shock and vibration resistant light sources runs on
- Major reduction in power costs, maintenance free
- Generate little heat
- No fluorescent flickering
- No danger of broken glass
- External power supply with high power factor & low harmonic current

Testing Data:

No.	Model	Power (W)	Lumen (LM)	LED	Beam Angle	Base	Input Voltage	PF	Color	CRI
1	ENSP-6WG24-01	6	560	Lumenmax 3014	120°	G24	85-265VAC	0.6	2800-3200K/ 4000-4500K/ 6000-6500K	>80
2	ENSP-6WG24-01D	6	560 Dimmable	Lumenmax 3014	120°	G24	85-265VAC	0.6	2800-3200K/ 4000-4500K/ 6000-6500K	>80
3	ENSP-6WE27-01	6	560	Lumenmax 3014	120°	E27	85-265VAC	0.6	2800-3200K/ 4000-4500K/ 6000-6500K	>80
4	ENSP-6WE27-01D	6	560 Dimmable	Lumenmax 3014	120°	E27	85-265VAC	0.6	2800-3200K/ 4000-4500K/ 6000-6500K	>80
5	ENSP-7WG24-01	7	720	Lumenmax 3014	120°	G24	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
6	ENSP-7WG24-01D	7	720 Dimmable	Lumenmax 3014	120°	G24	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
7	ENSP-7WE27-01	7	720	Lumenmax 3014	120°	E27	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
8	ENSP-7WE27-01D	7	720 Dimmable	Lumenmax 3014	120°	E27	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
9	ENSP-10WG24-01	10	960	Lumenmax 3014	120°	G24	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
10	ENSP-10WG24-01D	10	960 Dimmable	Lumenmax 3014	120°	G24	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
11	ENSP-10WE27-01	10	960	Lumenmax 3014	120°	E27	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
12	ENSP-10WE27-01D	10	960 Dimmable	Lumenmax 3014	120°	E27	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
13	ENSP-12WG24-01	12	1200	Lumenmax 3014	120°	G24	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
14	ENSP-12WG24-01D	12	1200 Dimmable	Lumenmax 3014	120°	G24	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
15	ENSP-12WE27-01	12	1200	Lumenmax 3014	120°	E27	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80
16	ENSP-12WE27-01D	12	1200 Dimmable	Lumenmax 3014	120°	E27	85-265VAC	0.95	2800-3200K/ 4000-4500K/ 6000-6500K	>80

● Packing:

Model	ENSP-6WG24-01(D) ENSP-6WE27-01(D) ENSP-7WG24-01(D) ENSP-7WE27-01(D)	ENSP-10WG24-01(D) ENSP-10WE27-01(D) ENSP-12WG24-01(D) ENSP-12WE27-01(D)
Carton (mm)	480×330×350	480×330×350
Quantity (PCS)	125	96
Net Weight/Gross Weight (Kg)	12.1/12.5	11.5/14.1

Warning:

1. It is non-waterproof.
2. Please do not touch it when they are light.
3. Please use traditional coop transformer and switch for power supply. Do not use traditional electronic transformer for power supply.
4. The angle of emitting light can be designed according to the client's requirements

